

**GASOIL  
 GAZOLE**



**TUYAU CARBURANT - EN ISO 6806 / DIN 73379 TYPE C**

FUEL HOSE - EN ISO 6806 / DIN 73379 TYPE C

REFERENCES		ID	OD	WP	BR/r	Dévidoir
AU ML	DEVIDOIR	mm	mm	bar	mm	ml
AGTMG00005	AGTMG00005-D20	4,5	9,5	20	25	20
AGTMG00006	AGTMG00006-D20	5,5	10,5	20	30	20
AGTMG00008	AGTMG00008-D15	7,5	12,5	15	40	15
AGTMG00010	AGTMG00010-D10	9	14	15	45	10
AGTMG00012		11	17,7	15	50	
AGTMG00015		14	21,2	15	65	
AGTMG00018		17	24	15	80	
AGTMG00022		21,5	30	15	95	
AGTMG00025		25	35,8	15	150	

- caoutchouc et tresse métallique galvanisée
- -35°C à +80°C
- Huile moteur, huile végétale, gazole, fuel, eau, glycols,




**TUYAU CARBURANT - DIN 73379 2A - ESSENCE**

FUEL HOSE - DIN 73379 2A - PETROL

REFERENCES		ID	OD	WP	BR/r	Dévidoir
AU ML	DEVIDOIR	mm	mm	bar	mm	ml
AGTCG00005	AGTCG00005-D15	4,5	10,5	10		15
AGTCG00006	AGTCG00006-D15	5,5	11,5	10		15
AGTCG00008	AGTCG00008-D15	7,5	13,5	10		15
AGTCG00010	AGTCG00010-D10	9	15	10		10
AGTCG00012		12	19	10		

- Caoutchouc et tresse textile noyé
- -40°C à +80°C
- 10 bars
- Essence, gazole, liquide de refroidissement (90°C), air



**GASOIL  
 CARBURANT**

**AV** AUTRES PRODUITS  
**AV** CONTACT