

ONDULEUX MÉTALLIQUE INOX STAINLESS STEEL HOSES



TUYAU ONDES PARALLÈLES NORMALES INOX AISI 316 RENFORCÉES PAR 1 TRESSE INOX AISI 304

STAINLESS STEEL HOSE - PARALLEL NARROW CORRUGATION - AISI 316L WITH 1 BRAID AISI 304

Référence	ID		OD		WP		BR/r		W
	mm	inch	mm	inch	bar	psi	statique	dynamique	
DI-TIOND15010006	6,40	1/4"	11,50		150	2175	25	100	0,300
DI-TIOND15010008	8,00	5/16"	13,10		135	1958	40	140	0,400
DI-TIOND15010010	9,50	3/8"	17,00		90	1305	40	200	0,450
DI-TIOND15010012	12,70	1/2"	19,90		80	1160	50	200	0,500
DI-TIOND15010016	15,90	5/8"	24,10		70	1015	50	200	0,600
DI-TIOND15010020	19,10	3/4"	29,50		64	928	70	200	0,650
DI-TIOND15010025	25,40	1"	36,90		50	725	90	250	0,800
DI-TIOND15010032	31,80	1 1/4"	43,70		40	580	110	250	1,500
DI-TIOND15010040	38,40	1 1/2"	53,90		30	435	130	350	1,650
DI-TIOND15010050	50,80	2"	68,40		28	406	175	410	1,800
DI-TIOND15010065	65,40	2 1/2"	84,00		24	348	200	450	2,400
DI-TIOND15010080	76,60	3"	98,50		18	261	205	560	3,000
DI-TIOND15010100	103,00	4"	121,00		16	232	230	920	3,700
DI-TIOND15010125	127,50	5"	154,00		12,5	181	325	1160	5,750
DI-TIOND15010150	151,50	6"	180,00		10	145	375	1320	6,900

Tube :	onduleux inox aisi 316 ou 321 - ondes parallèles normales
Armature :	1 tresse inox aisi 304
Revêtement :	vapeur, fluides a très basses et très hautes températures, air, gaz, bitume, échappements
Utilisation :	moteurs, vide - bonne résistance aux vibrations
C.d.S. :	4:1
Température :	-270°C / +700°C (-454°F / +1292°F)
Normes :	soudure tig - les flexibles peuvent être fabriqués sur demande dans nos ateliers étude et réalisation pour toutes vos demandes spécifiques
Tube :	<i>Stainless steel sinuous AISI 316 - closed parallel waves</i>
Armature :	<i>1 stainless steel braid AISI 304</i>
Coating :	<i>Vapor, fluids in very low and very high-temperature, aor, gas, asphalt, engine exhaust - good</i>
Application :	<i>resistance in the vibrations</i>
C.d.S. :	<i>Weld TIG - Flexible hoses could be assembled in our workshops on request</i>
Temperature :	<i>All your specific requests analyzed by our technical service</i>
Norms :	