



# COMPENSATEURS INOX

## COMPENSATEUR D'ÉCHAPPEMENT À BRIDE FIXE PN3.5



jusqu'à + 400°C

### COMPOSITION



Soufflet en acier  
inoxydable AISI 321



Tube et manchettes en acier

### DONNÉES TECHNIQUES

Référence	DN (mm)	Mouvement axial (+/- mm)	Mouvement latéral (+/- mm)	LB (mm)	D (mm)	K (mm)	b (mm)	Ø X nb (mm)
DI-CPIE.BF3.5.080	80	25	9.5	100	200	160	10	18 X 8
DI-CPIE.BF3.5.100	100	29	10	100	220	180	10	18 X 8
DI-CPIE.BF3.5.125	125	29	8	105	250	210	10	18 X 8
DI-CPIE.BF3.5.150	150	29	7.5	120	285	240	10	22 X 8
DI-CPIE.BF3.5.175	175	30	6.5	180	315	270	10	22 X 8
DI-CPIE.BF3.5.200	200	30	6	180	340	295	10	22 X 8
DI-CPIE.BF3.5.225	225	30	5	180	370	325	10	22 X 8
DI-CPIE.BF3.5.250	250	30	4.5	257	395	350	10	22 X 16
DI-CPIE.BF3.5.350	350	35	5	297	505	460	12	22 X 16
DI-CPIE.BF3.5.400	400	35	4.5	297	565	515	12	26 X 12
DI-CPIE.BF3.5.300	300	32	4.7	303	445	400	12	22 X 12

[www.isoflex.fr](http://www.isoflex.fr)

Tel : +33(0)2 41 39 98 98 - [contact@isoflex.fr](mailto:contact@isoflex.fr)

ANGERS (49) - LOUDEAC (22) - NANTES (44) - CAEN (14) - AVIGNON (84) - ORLÉANS (45)