


EMBOUTS INTERLOCK ORFS

EMBOUT FEMELLE COUDE 90°



DONNÉES TECHNIQUES

Filetage UNF - joint facial



Référence	Désignation	S (int. tuyaux)			Dimensions			
		module	inch	mm	filetage	F/p	pas	D.I
IFORF91010	IN 16 FORF 1" 90	10	5/8"	15,9	1"	14	1,814	23,45
IFORF91012	IN 16 FORFS 1"3/16 90	10	5/8"	15,9	1"3/16	12	2,116	27,87
IFORF91210	IN 19 FORF 1" 90	12	3/4"	19	1"	14	1,814	23,45
IFORF91212	IN 19 FORFS 1"3/16 90	12	3/4"	19	1"3/16	12	2,116	27,87
IFORF91216	IN 19 FORFS 1"7/16 90	12	3/4"	19	1"7/16	12	2,116	34,22
IFORF91612	IN 25 FORFS 1"3/16 90	16	1"	25,4	1"3/16	12	2,116	27,87
IFORF91616	IN 25 FORFS 1"7/16 90	16	1"	25,4	1"7/16	12	2,116	34,22
IFORF91620	IN 25 FORFS 1"11/16 90	16	1"	25,4	1"11/16	12	2,116	40,57
IFORF92020	IN 32 FORFS 1"11/16 90	20	1"1/4	31,8	1"11/16	12	2,116	40,57
IFORF92024	IN 32 FORFS 2" 90	20	1"1/4	31,8	2"	12	2,116	48,51
IFORF92424	IN 38 FORFS 2" 90	24	1"1/2	38,1	2"	12	2,116	48,51

PRODUITS SIMILAIRES

Cet embout existe également en mâle droit et femelle droit ou coudé 45° et 90° courbe haute.

www.isoflex.fr

Tel : +33(0)2 41 39 98 98 - contact@isoflex.fr

ANGERS (49) - LOUDEAC (22) - NANTES (44) - CAEN (14) - AVIGNON (84) - ORLÉANS (45)